


A diagram of a beam of total length 450 units, supported at both ends. A triangular load is applied, starting at 0 units at the left support, peaking at 240 units at a distance of 227 units from the left support, and returning to 0 units at the right support. The beam is represented by a horizontal line with upward-pointing triangles at the supports. The load is represented by a downward-pointing triangle above the beam. The dimensions 240 and 227 are indicated below the beam with tick marks.



18.5  
19 18.5  
③  $\phi 6$  L = 84cm

ZESTAWIENIE ZBROJENIA									
BELKA ŻELBETOWA    poz. 3.1.7									
Nr	Średnica [mm]		Długość [cm]	Ilość [szt.]	DŁUGOŚĆ CAŁKOWITA				
	Φ	#			St0S		B500SP		
					Φ 6	Φ8	# 12	# 16	# 20
1		12	518	3			15,54		
2		12	488	3			14,64		
3	6		84	34	28,56				
DŁUGOŚĆ OGÓŁEM [m]					28,56	0	30,18	0	
MASA JEDNOSTKOWA [kg/m]					0,222	0,4	0,888	1,59	
MASA OGÓŁEM [kg]					6,34	0,00	26,80	0,00	
MASA RAZEM ( 1 elem. ) [kg]					6,34		26,80		

**1:25**

Data	Skala rysunku	Nr rysunku
2023.09.25	1:25	K-2.7