

MicroGard Filter

single use bacteria filter with integrated mouthpiece

Art....-No 892381



Specifications:

Inspiratory Resistance:

< 0.4 cm H₂O/L/S at 1 L/S

Expiratory Resistance:

< 0.4 cm H₂O/L/S at 1 L/S

Filter Efficiency against cross contamination:

%BFE \geq 99.999 % (Nelson Test Lab)

%VFE \geq 99.999 % (Nelson Test Lab)

Filter Volume: 55 mL

Connections: 30 mm ID. 30 mm OD. Tapered ports

Connections (filter with integrated mouthpiece): 30 mm ID.

Tapered port Single patient use

This device is not made with natural rubber latex

Ambient Conditions:

Temperature: 0 °C to 42 °C

Relative humidity: keep dry

Filtr MicroGard

jednorazowego użytku filtr ze zintegrowanym ustnikiem

Nr kat. 892381



Dane techniczne:

Opór przy wdechu:

< 0,4 cm H₂O/L/S przy przepływie

1 L/S Opór przy wydechu:

< 0,4 cm H₂O/L/S przy przepływie

1 L/S Efektywność filtracji:

%BFE \geq 99.999 % (Nelson Test Lab)

%VFE \geq 99.999 % (Nelson Test Lab)

Objętość filtra: 55 mL

Przylączy: 30 mm, średnica wewnętrzna. 30 mm, średnica zewnętrzna.

Otwory stożkowe

Przylączy (filtr ze zintegrowanym ustnikiem): 30 mm, średnica wewnętrzna. Otwór stożkowy

Jednorazowego użytku

Bez zawartości lateksu

Warunki otoczenia:

Temperatura: od 0 °C do 42 °C

Wilgotność względna powietrza: Suche miejsce