







































Obiekt: Budynek Uniwersytetu Łódzkiego "Motyl".									MKT	
Treść rys.: Rzut piwnic. Wzmocnienia i wyburzenia.										
2024-02-07		SPECYFIKACJA DO RYSUNKU NR:			MTL-PT-K-07				1 / 3	
ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	Φ	Φ	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			A-0	A-IIIIN		I	na 1 el.			
1	2	3	4	5	6	7	8	9	10	11
Ściana "Sc-0.1[gr.25cm]"	3		-	12	334.0	-	106	354.0	314.3	Σ= 610.3
	4		-	10	476.6 mb	-	-	476.6	293.8	
	11		-	4.5	31.0	-	56	17.4	2.2	
Zbrojenie trzpienia "TZ-1.1"	2		-	16	402.0	-	8	32.2	50.8	Σ= 68.8
	7		-	8	145.0	-	9	13.1	5.1	
	8		-	8	142.0	-	23	32.7	12.9	
Zbrojenie trzpienia "TZ-10.1"	2		-	16	402.0	-	12	48.2	76.1	Σ= 109.8
	6		-	8	158.0	-	46	72.7	28.7	
	10		-	8	139.0	-	9	12.5	4.9	
Zbrojenie trzpienia "TZ-11.1"	1		-	16	512.0	-	12	61.4	97.0	Σ= 138.0
	6		-	8	158.0	-	56	88.5	34.9	
	9		-	8	141.0	-	11	15.5	6.1	
Zbrojenie trzpienia "TZ-12.1"	1		-	16	512.0	-	12	61.4	97.0	Σ= 131.9
	6		-	8	158.0	-	56	88.5	34.9	
Zbrojenie trzpienia "TZ-13.1"	1		-	16	512.0	-	12	61.4	97.0	Σ= 125.7
	6		-	8	158.0	-	46	72.7	28.7	
Zbrojenie trzpienia "TZ-15.1"	1		-	16	512.0	-	12	61.4	97.0	Σ= 125.7
	6		-	8	158.0	-	46	72.7	28.7	
MTL-PT-K-07_spec						 Adelante Solutions © 2014 - 2024				

Obiekt: Budynek Uniwersytetu Łódzkiego "Motyl".									MKT	
Treść rys.: Rzut piwnic. Wzmocnienia i wyburzenia.										
2024-02-07		SPECYFIKACJA DO RYSUNKU NR:			MTL-PT-K-07				2 / 3	
ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	Φ	Φ	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			A-0	A-IIIIN		l	na 1 el.			
1	2	3	4	5	6	7	8	9	10	11
Zbrojenie trzpienia "TZ-16.1"	1		-	16	512.0	-	12	61.4	97.0	$\Sigma=$ 125.7
	6		-	8	158.0	-	46	72.7	28.7	
Zbrojenie trzpienia "TZ-17.1"	1		-	16	512.0	-	12	61.4	97.0	$\Sigma=$ 125.7
	6		-	8	158.0	-	46	72.7	28.7	
Zbrojenie trzpienia "TZ-2.1"	2		-	16	402.0	-	8	32.2	50.8	$\Sigma=$ 68.8
	7		-	8	145.0	-	9	13.1	5.1	
	8		-	8	142.0	-	23	32.7	12.9	
Zbrojenie trzpienia "TZ-3.1"	2		-	16	402.0	-	8	32.2	50.8	$\Sigma=$ 68.8
	7		-	8	145.0	-	9	13.1	5.1	
	8		-	8	142.0	-	23	32.7	12.9	
Zbrojenie trzpienia "TZ-4.1"	2		-	16	402.0	-	12	48.2	76.1	$\Sigma=$ 104.8
	6		-	8	158.0	-	46	72.7	28.7	
Zbrojenie trzpienia "TZ-5.1"	2		-	16	402.0	-	8	32.2	50.8	$\Sigma=$ 68.8
	7		-	8	145.0	-	9	13.1	5.1	
	8		-	8	142.0	-	23	32.7	12.9	
Zbrojenie trzpienia "TZ-6.1"	2		-	16	402.0	-	8	32.2	50.8	$\Sigma=$ 68.8
	7		-	8	145.0	-	9	13.1	5.1	
	8		-	8	142.0	-	23	32.7	12.9	
MTL-PT-K-07_spec						 Adelante Solutions © 2014 - 2024				

