


Site 1

## Luminaire layout plan



Manufacturer	Noch kein DIALux Mitglied	P	10.0 W
Article name		$\Phi_{\text{Luminaire}}$	2000 lm
Fitting	1x		

### Individual luminaires

X	Y	Mounting height	Luminaire
449.064 m	19.914 m	4.050 m	1
408.564 m	19.114 m	4.050 m	2
354.364 m	17.814 m	4.050 m	3
311.364 m	16.514 m	4.050 m	4
268.464 m	14.814 m	4.050 m	5
225.664 m	13.314 m	4.050 m	6
182.664 m	11.814 m	4.050 m	7
137.764 m	10.214 m	4.050 m	8
97.164 m	8.514 m	4.050 m	9
54.464 m	6.914 m	4.050 m	10


Site 1

Luminaire list

$\Phi_{total}$	$P_{total}$	Luminous efficacy				
20000 lm	100.0 W	200.0 lm/W				
pcs.	Manufacturer	Article No.	Article name	P	$\Phi$	Luminous efficacy
10	Noch kein DIALux Mitglied			10.0 W	2000 lm	200.0 lm/W

Site 1 (Light scene 1)

## Calculation objects



Site 1 (Light scene 1)

**Calculation objects**

## Calculation surfaces

Properties	$\bar{E}$	$E_{min}$	$E_{max}$	$U_o (g_1)$	$g_2$	Index
Calculation surface 16 Perpendicular illuminance Height: 0.000 m	7.24 lx	0.10 lx	27.9 lx	0.014	0.004	CG1

Utilisation profile: DIALux presetting (5.1.4 Standard (outdoor transportation area))

Site 1 (Light scene 1)  
Calculation surface 16



Properties	$\bar{E}$	$E_{min}$	$E_{max}$	$U_o (g_1)$	$g_2$	Index
Calculation surface 16 Perpendicular illuminance Height: 0.000 m	7.24 lx	0.10 lx	27.9 lx	0.014	0.004	CG1

Utilisation profile: DIALux presetting (5.1.4 Standard (outdoor transportation area))