


# SCHODY ZEWNĘTRZNE BIEG 1



ZESTAWIENIE STALI DLA SCHODÓW ZEWNĘTRZNYCH						
Lp.	Symbol	Ilość w elem.	Masa [kg/m]	Długość [m]	Waga [kg]	Stal
1	#12	7	0,888	3,55	22,07	Rb500W
2	#12	7	0,888	3,56	22,13	Rb500W
3	#8	28	0,4	1,33	14,90	Rb500W
4	#12	7	0,888	3,46	21,51	Rb500W
5	#12	8	0,888	4,45	31,61	Rb500W
6	#12	8	0,888	4,38	31,12	Rb500W
7	#12	8	0,888	4,88	34,67	Rb500W
8	#12	8	0,888	4,30	30,55	Rb500W
9	#8	30	0,4	1,63	19,56	Rb500W
10	#12	4	0,888	1,42	5,04	Rb500W
11	#12	8	0,888	1,60	11,37	Rb500W
12	#6	16	0,222	1,36	4,83	Rb500W
					<b>249,34</b>	

BETON C25/30  
STAL AIIIIN (Rb500W)  
OTULINA 30mm, FUNDAMENTY 50mm

Zbrojenie pozostałej części schodów pokazano na rys. 2-K